





IBZA 10: Compact Multi-purpose Loudspeaker



MAIN APPLICATIONS

- Portable live Sound reinforcement
- Museums and AV spaces
- Stand alone system
- Fixed Installations
- Main FOH or additional reinforcement

MAIN FEATURES

- Compact two-way passive system
- 10"- LF / 1 x 1" HF compression driver
- 8 Ω nominal impedance
- Mounting accessories

The **IBZA10** is a trapezoidal compact full-range loudspeaker, which houses a long excursion 10" low frequency driver and high frequency 1" compression driver. It has a highly extended bass performance for such a small volume, with a well-balanced mid and high section.

The two-way system is designed for applications where high output is required with a moderate amount of low frequency energy from a compact enclosure. It has been designed for use as stand-alone full-range speaker or together with a sub woofer (E.G. SW115 or SW118M). The horn can be rotated through 90° in order to swap the horizontal and vertical dispersion patterns.

The box houses multiple internal rigging points for ground-support, truss and wall mounting, pole mount socket, and speakON® connectors.

The cabinet has been made with the latest techniques ensuring a perfect and rigid construction. Weatherized finish is provided, as the enclosure is coated with rugged Poliurea texture finish and protected with special grills.

The system is available in both passive (IBZA10) and active (bi-amped) version without networking (IBZA10A) or with networking remote PC control (IBZA10-PCC3)

Frequency Response	56 Hz - 20 kHz*
Frequency Response: Free Field	80 Hz - 17 kHz ±3 dB
SPL (1m)	123 dB SPL
Maximum Peak SPL	129 dB SPL
Transducers: Low/High Frequency	1 x 10" cone drivers and 1 x 1" HF driver on a rotatable exponential horn
Sensitivity (1W/1m)	97dB
Dispersions (HxV)	70° x 50°
Recommended amplifier	PA900/PA4.450/T6-44
Power (Nominal)	350 W
Power (Peak)	700 W
Rate Impedance	8 Ω
Input Connectors	IN: 1xNL4 SpeakON® LINK: 1 X NL4 SpeakON®
NET Weight	15 kg (33,6 lbs)
Dimensions	500 x 302 x 320 mm (HxWxD) (19.68" x 11.89" x 12.6")
Construction	16mm birch plywood. Finished in black semi-matt textured Polyurea weatherized coating.
Protective Grille	Powder coated perforated steel with acoustically transparent reticulated foam

*Recommended maximum operating frequency range. Response depends on loading conditions and room acoustics.



Pº Ind. Monte Boyal, C/Encinar 282
45950 Casarrubios del Monte (Toledo), SPAIN.
Phone: +34 918 170 110
Fax: +34 918 183 053
www.tecnaire.com
sales@tecnaire.com