



CS-360 is a simple and affordable Conference discussion system. With exquisite design, focusing on application of various conferences, the newly developed sound activate mode, the participants don't need operating manually, just speaking to microphones directly, the microphone unit can be started to speak, simple to use, fully applicable to the various conference locations.

### Product Specification



CS-360  
Central Controller

Chassis Pecifications:	EIA Standard Rack 1U
Supply Voltage:	90-264V AC or 127-370V AC , 47-63Hz
Static Power Consumption:	6W
Rated Power:	75W/24V
Maximum Power:	100W/24V
XLR Balances Caron Maximum Output Level:	14.6dBu
Maximum output level of the 6.35mm balance socket:	14.6dBu
RCA lotus socket maximum output level:	9.8 dBu
RCA lotus socket maximum input level:	3.2 dBu
Conference Unit Extension:	Anti drop 9P aviation plug x 1 , Network port (female) x1
Video Input Port:	BNC x 4
Video Output Port:	BNC x 1
Video Interface Impedance:	75Ω
9 pin serial port control interface:	DB9 Female plug x 1
Rs-232 control protocol interface:	5P Phoenix terminal X 1
Rs-422 control protocol interface:	5P Phoenix terminal X 1
Dante interface:	RJ45x1
Audio output:	XLRM x 1 , 6.35mm jack x 1 , RCA Lotus x 1
Audio input:	RCA Lotus x 1
Screen type:	OLED
Key mode:	Touch style
Weight:	About 2.3kg
Dimension (mm):	410 (W)×206 (D)×43 (H)

### Key Features

#### Practical Function

- Adopt the OLED display, can display the microphone status, operating mode, central controller status, the number of speaker, etc.
- 4 kinds of conference mode selection: FIFO, Automatic(with limiting time), Request, Sound activate.
- The central controller can select the number of speakers, active 2/3/4 microphones in a time.
- Support camera tracking, through the serial port RS-232 or RS-422communication protocol control up to 4 cameras, compatible with VISCA, PELCO-D, PELCO-P 3 kinds of camera control code protocol.
- With 4 video inputs and 1 video output port, SD and HD SDI video inputs and outputs are supported. HD SDI supports HDcctv1.0, HD-SDI (ST292), 3G-SDI (ST424) and SD-SDI (259).
- 9-pin serial port control interface can be connected to intelligent control system for camera tracking.
- Support Dante protocol, flexible to meet various engineering solutions.
- The newly developed high-voltage, low-current power supply system minimizes line voltage losses and minimizes the effects of overly long connecting cables. One cable to connect more conference units makes installation easier.
- Adopt using anti shedding aviation cable hand in hand connection mode, the connection is simple, reliable and stable, the whole system required engineering and installation costs can be reduced.

#### Flexible Expanding

- It is easy to expand and change configuration. The central controller connect up to 30 microphone units. If connect the EXP-124W, can connect up to 110 microphone units.
- Connecting telephone coupler can be applied directly to a remote call meeting.

#### Flexible Speaking

- CS-360C chairman unit has the priority to override all delegate units, to control the atmosphere of the meeting.

#### Four Speech Mode:

- ① Time limiting: The speech time limit can be set to 1-60 minutes, and the speech will be automatically closed when the time is up. After reaching the power-on quantity, when another representative wants to speak, it will automatically enter the request-to-speak registration queue.
- ② FIFO: FIFO mode (default). After reaching the power-on number, the speaking unit that was opened first is closed by the subsequent speaking unit.
- ③ Request: The speaking of the representative unit needs to be approved by the chairman unit or the operator. In this mode, the chairman unit always keeps the normally open state.
- ④ Voice Activated: When the microphone is turned on by voice, manual operation is not required. After the number of power-on is reached, the speaking unit that is turned on first is turned off by the subsequent speaking unit.

#### Multiple Ports

- With record output can connect the recorder, all records can be fully recorded and saved, also can connect the external audio device.
- With anti drop 9P aviation plug and Cat5 TypeB network port

#### Clear Sound Quality

- With automatic gain audio processing circuit, prevent feedback effectively and improve the clarity of the whole system.



CS-360C  
Chairman unit

CS-360D  
Delegate Unit

Polar Pattern:	Super Cardioid Condenser
Frequency Response:	50Hz-18KHz
Sensitivity:	-43dB+/-3dB(0dB=1V/Pa,f=1KHz)
SPL:	110dB(THD < 5%, f=1KHz)
S/N (A weighted):	> 60dBA ( THD < 1% , f=1 KHz )
Distortion :	< 0.1%
Power Supply:	24V DC(supplied by the receiver)
Maximum Power of Speakers:	0.72W
Weight:	670g
The Length of Microphone :	147(L)×115 (W)×218(H)
Unit Interface:	Wired network port