

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it

Technical Datasheet **Firestop®**

tasker® C230 – 1x75Ω+2x0,75 mm²

Special Video Cable



CATEGORY Special Video Cable 75Ω (See video Catalogue)
APPLICATIONS Video surveillance and cameras.

A: Soft **Flame Retardant PVC sheath**. White Color.
 Outer cable Diameter Ø 10,50 (± 0,20) mm.

75 Ω Video

- B:** Sheath in **Flame Retardant PVC**. White Color.
Diameter Ø 6,20 (± 0,20) mm.
- C:** Shielding in O.F.C. Red Copper braid covering 98%.
- D:** Insulation in transparent **compact PE**.
Diameter Ø 3,70 (± 0,20) mm.
- E:** CW stiff wire 1x0,58 mm.
Nom. Cross section 1x0,26 mm²

Insulated cores

- F:** Sheaths in **Flame Retardant PVC**, colored one Black and one Red.
Diameter Ø 1,90 (± 0,20) mm.
- G:** Stranded formation 24x0,20 mm in OFC red copper
Nom. Cross section 2x0,75 mm².

MARKING **CUSTOM** **PRODUCTION**

TASKER
 This product may be custom produced also in **L.S.Z.H.** polymer, **PE**, **PUR**,
 with or without Metallic Armor.

MILAN S.r.l. a socio unico

Head Office – Export department: **Ufficio Commerciale e Centro Distribuzione**
 Viale Europa, 74 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158 T. +39 02 9039.0037-0059
 F. +39 02 9039.4551 F. +39 02 9039.0049
 www.taskercables.com www.tasker.it

Coaxial Properties

insulated Conductors Resistance	21,93 Ω/Km
Coax Conductor Resistance	158 Ω/Km
Coax Capacity Core/Shield	67 pF/mt
Coax Impedance	75 Ω
Max Rated Voltage	49V
Operative Temperature	-20/+70°C

Attenuation dB/100 m.

50 MHz	7,40
100 MHz	10,70
200 MHz	15,70
400 MHz	22,70
800 MHz	33,60
1000 MHz	38,00

USE	X	Indoor	Interno Edificio
Impiego	X	Outdoor Limited	Esterno Limitato
		Outdoor	Esterno
		Outdoor Direct Burial	Esterno Interrato

INSTALLATION	X	Fixed	Fissa
Posa	X	Restricted Mobile	Mobile Limitata
		Mobile	Mobile
		Mobile in Drag Chain	Mobile in Catena

INFORMATION	X	RoHS2 Compliant
Informazioni	X	Ver. A / 16.05.17