



Amphenol manufacture a large range of connectors to suit cables other than those listed below, for example Belden YR23769 and 46899, please contact us to discuss your specific requirements.

[Assembly Instructions Page 66-67](#)

[Specifications: Page 68-69](#)

[Panel Cutouts: Page 70](#)

### NOTES

**CAI = Cable Assembly Instructions**

**PLT = Plating Code (Refer Specifications)**

**INS. = Cable Insulator Material (Refer Specifications)**

PRODUCT - FIGURE	DRAWING Dimensions in mm (inches)	DESCRIPTION & CABLE TYPE RG-/U	NOTES			75Ω TYPE	PART NUMBER
			CAI	PLT.	INS.		
	 $\phi 14.5$ [ $\phi 0.570$ "] $\phi 7.6$ [ $\phi 0.299$ "] T1(X)=34.3[1.350"] T2(X)=30.7[1.210"]	<b>Crimp Plug</b> RG-6 Type .295" O.D. max. Belden 9248, 1694A (Single Shield)	C31	P15	D1	T1	31-70000
			C32	P7	D26	T2	31-71000 - RFX
	 $\phi 14.5$ [ $\phi 0.570$ "] $\phi 6.6$ [ $\phi 0.260$ "] T1(X)=31.7[1.248"] T2(X)=29.8[1.170"]	<b>Crimp Plug</b> 59, 62 Belden 8241, 8263, 8279, 9209	C31	P16	D1	T1	31-70008
			C32	P7	D26	T2	31-71008 - RFX
	 $\phi 14.5$ [ $\phi 0.570$ "] $\phi 6.6$ [ $\phi 0.260$ "] T1(X)=31.8[1.252"] T2(X)=29.8[1.170"]	<b>Crimp Plug</b> 59 Type (20AWG CC) Belden 1426A, 1505A, 9100, 9278	C31	P15	D1	T1	31-70008 - 3000
			C32	P7	D26	T2	31-71008 - 1RFX
	 $\phi 14.5$ [ $\phi 0.570$ "] 31.7 [1.248"] $\phi 6.6$ [ $\phi 0.260$ "]	<b>Crimp Plug</b> 59 Type centre conductor, Belden 1505A, 1426A, 9659, 9259, 9240, 8212, 9274, 9275, 9100	C31	P15	D1	T1	31-70008 - 1000
	 $\phi 14.5$ [ $\phi 0.570$ "] $\phi 3.0$ [ $\phi 0.118$ "] T1(X)=33.5[1.319"] T2(X)=30.2[1.190"]	<b>Crimp Plug</b> Miniature Coax, 179, 187	C31	P15	D1	T1	31-70013
			C32	P17	D26	T2	31-71013 - RFX
	 $\phi 14.5$ [ $\phi 0.570$ "] 34.5 [1.358"] $\phi 8.5$ [ $\phi 0.335$ "]	<b>Crimp Plug</b> Double Shield 59 (20 AWG CC)	C31	P15	D1	T1	31-70222