




9180 Paired - Digital Video Time Code

	<p>For more information please call 1-800-Belden1</p> <p><u>See Put-ups and Colors</u></p>
-----------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------------------------------

Description:

110 Ohm, 26 AWG stranded (7x34) .018" TC conductors, Datalene® insulation, twisted pair, Beldfoil® shield (100% coverage), 26 AWG stranded TC drain wire, PVC jacket.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Pairs	1
Total Number of Conductors	2
AWG	26
Stranding	7x34
Conductor Diameter	.019 in.
Conductor Material	TC - Tinned Copper

INSULATION:

Insulation Material Trade Name	Datalene®
Insulation Material	FHDPE - Foam High Density Polyethylene
Insulation Diameter	.049 in.
Lay Length	1.5 in.
Twists/ft.	8

Pair Color Code Chart :

Number	Color
1	Black & White

OUTER SHIELD:

Outer Shield Material Trade Name	Beldfoil®
Outer Shield Type	Tape
Outer Shield Material	Aluminum Foil-Polyester Tape w/Shorting Fold
Outer Shield % Coverage	100 %

OUTER SHIELD DRAIN WIRE :

Outer Shield Drain Wire AWG	26
Outer Shield Drain Wire Stranding	7x34
Outer Shield Drain Wire Conductor Material	TC - Tinned Copper

OUTER JACKET:



9180 Paired - Digital Video Time Code

Outer Jacket Material	PVC - Polyvinyl Chloride
-----------------------	--------------------------

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	.144 in.
--------------------------	----------

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-40°C To +75°C
Non-UL Temperature Rating	75°C
Bulk Cable Weight	9.4 lbs/1000 ft.
Max. Recommended Pulling Tension	10.5 lbs.
Min. Bend Radius (Install)	2 in.

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

NEC/(UL) Specification	CMR
CEC/C(UL) Specification	CMG
EU CE Mark (Y/N)	No
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004
Other Specification	AES/EBU

FLAME TEST:

UL Flame Test	UL1685 FT4 Loading
CSA Flame Test	FT4

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
--------------	---

ELECTRICAL CHARACTERISTICS:

Nom. Characteristic Impedance	110 Ohms
Nom. Inductance	.23 µH/ft
Nom. Capacitance Conductor to Conductor @ 1 KHz	13.0 pF/ft
Nom. Cap. Cond. to Other Cond. & Shield @ 1 KHz	26 pF/ft
Nominal Velocity of Propagation	76 %
Nominal Delay	1.34 ns/ft
Nom. Conductor DC Resistance @ 20 Deg. C	37.3 Ohms/1000 ft
Nominal Outer Shield DC Resistance @ 20 Deg. C	23.1 Ohms/1000 ft
Nom. Attenuation (dB/100 ft) :	

9180 Paired - Digital Video Time Code

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Nom. Attenuation (dB/100 ft.)
	.38			0.84
	.77			1.18
	1.0			1.34
	1.5			1.54
	2.0			1.69
	3.1			1.92
	4.1			2.14
	5.6			2.40
	8.2			2.75
	11.3			3.09
	12.3			3.18
	24.6			4.20

Max. Operating Voltage - UL 300 V RMS
 Max. Recommended Current 1.9 Amps per conductor @ 25°C

NOTES:

Notes For cross-connect use with 7891A (et al.) Digital Audio Snake Cables.

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
9180 0601000	2 #26 FHDPE FS FRPVC	1000	12	CHROME	C
9180 Z4B1000	2 #26 FHDPE FS FRPVC	1000	12	VIO Z4B	

C = CRATE REEL PUT-UP.

Revision Number: 1 Revision Date: 08-24-2005

© 2005 Belden Wire & Cable Company
 All Rights Reserved.

Although Belden Electronics Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden CDT Electronics Division believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs.(San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003); EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

BELDENCable™

9180 Paired - Digital Video Time Code